

AMENDMENTS TO THE CLAIMS:

Please amend the claims as follows.

1. (Currently Amended) An electronic equipment comprising:
a display device configured to display information and including a display surface;
a touch sensor arranged on at least a part of the display surface;
a guide portion configured to protrude from a surface of the touch sensor and to fringe the surface with a line ~~including~~ configured by one of a concave portion and a convex portion as a whole, including a vertex configured as a reference position; and
a controller configured to control an adjustment value in accordance with a direction of a slide operation along said guide portion from the reference position.
2. (Original) The electronic equipment as claimed in claim 1, wherein the controller sets the adjustment value to a predetermined reference value when the reference position is depressed.
3. (Original) The electronic equipment as claimed in claim 2, wherein the controller changes the adjustment value from the reference value when the slide operation is performed after the reference position is depressed.
4. (Previously Presented) The electronic equipment as claimed in claim 1 further comprising:

a notification unit configured to provide a notification that the reference position is depressed.

5. (Original) The electronic equipment as claimed in claim 1, wherein the controller controls an adjustment value of an output level of an acoustic signal.

6. (Previously Presented) The electronic equipment as claimed in claim 1, wherein said touch sensor includes one of a display function and a switch function.

7. (Previously Presented) The electronic equipment as claimed in claim 1, wherein said touch sensor arranged on said at least a part of said display surface is configured to be proximate to said guide portion.

8. (Previously Presented) The electronic equipment as claimed in claim 1, comprising:

a graphical image displayed on said display device in said surface of said touch sensor, wherein said graphical image corresponds to said reference position.

9. (Previously Presented) The electronic equipment as claimed in claim 8, wherein said graphical image represents an initial value in a parameter adjustment range.

10. (Previously Presented) The electronic equipment as claimed in claim 8, comprising:

second and third graphical images displayed on said display device in said surface of said touch sensor on either side of said graphical image, wherein said second and third graphical images represent one of a value to be increased and a value to be decreased from said initial value in a parameter adjustment range.

11. (Currently Amended) A method of controlling electronic equipment, a touch sensor arranged on at least a part of ~~said~~ a display surface, a guide portion configured to protrude from a surface of said touch sensor and to fringe said surface with a line ~~including~~ configured by either a concave portion or a convex portion as a whole, including a vertex configured as a reference position, said method comprising:

guiding a finger along said guide portion to said reference position; and[[,]]

receiving a contact input on said surface of said touch sensor adjacent to said reference position based on guiding said finger along said guide portion to said reference position.

12. (Previously Presented) The method of controlling electronic equipment as claimed in claim 11, further comprising:

displaying a graphical image on said display device in said surface of said touch sensor, wherein said graphical image represents an initial value in a parameter adjustment range and corresponds to said reference position.

13. (Previously Presented) The method of controlling electronic equipment as claimed in claim 12, further comprising:

displaying second and third graphical images displayed on said display device in said surface of said touch sensor on either side of said graphical image, wherein said second and third graphical images represent one of a value to be increased and a value to be decreased from said initial value in a parameter adjustment range.

14. (Currently Amended) The method of controlling electronic equipment as claimed in claim 11, further comprising:

receiving sliding contact input on said surface of said touch [[a]] sensor adjacent to said reference position; and[[,]]

inputting said adjustment value to said controller based on receiving said sliding contact input.

15. (Previously Presented) The method of controlling electronic equipment as claimed in claim 14, wherein receiving sliding contact input on said surface of said touch sensor in a first direction inputs a positive adjustment value to said controller.

16. (Previously Presented) The method of controlling electronic equipment as claimed in claim 14, wherein receiving sliding contact input on said surface of said touch sensor in a second direction inputs a negative adjustment value to said controller.

17. (Previously Presented) The method of controlling electronic equipment as claimed in claim 11, further comprising:

storing a present value of an adjustment parameter in response to receiving said

contact input on said surface of said touch sensor adjacent to said reference position.

18. (Previously Presented) The method of controlling electronic equipment as claimed in claim 17, further comprising:

determining whether said slide operation is performed on said surface of said touch sensor.

19. (Previously Presented) The method of controlling electronic equipment as claimed in claim 18, further comprising:

adding said adjustment value to said stored present value of an adjustment parameter in response to determining whether said slide operation is performed; and

controlling an output parameter based on adding said adjustment value to said stored present value of an adjustment parameter.

20. (Currently Amended) An electronic equipment comprising:

display ~~device~~ means ~~configured to display~~ for displaying information, said display means and including a display surface means;

touch sensor means for sensing a touch, said touch sensor means being arranged on at least a part of said display surface means;

guide ~~portion~~ means configured to protrude from a surface of said touch sensor means and to fringe the surface with a line ~~including~~ configured by one of a concave portion and a convex portion as a whole, including a vertex configured as a reference position; and

~~controller control~~ means ~~configured to control~~ for controlling an adjustment value in

Application No. 10/664,080

7

Docket No. C14-161312M/NJK

accordance with a direction of a slide operation along said guide means from the reference position.